

MODBUS TCP Server, RTU slave to CANopen Master, 3 in 1 Gateway, 1 x RJ45, 1 x COM, 1 x CAN, -25 - +75°C, 10 - 30VDC

FEATURES

- Ethernet Gateway for CANopen networks and Modbus RTU
- 1 x RJ45 10 / 100Mbps
- Protocol: Modbus TCP Server
- 1 x RS232 / RS485 port (non-isolated)
- Modbus RTU slave
- Baud rate: 1200-115200
- 1 x CAN port
- CANopen
- CAN Baud rate: 10K - 1M
- Built-in 120 ohm termination
- Dimensions: 122 x 72 x 33 mm
- Supply voltage : 10 - 30VDC, 2,5Watt
- Operating temperature: -25 - + 75 ° C
- DIN bracket



SPECIFICATIONS

Operating Temp.	:	-25 - +75°C
Forsyning	:	10 - 30VDC, 2.5Watt
Mål og vægt	:	122 x 72 x 33 mm
Netværk	:	1 x RJ45 10/100Mbit
Porte	:	1 x RS232 og 1 x RS485 (en kan vælges)
Porte	:	1 x CAN bus - CiA 301 v4.02
Skærm	:	5 cifret 7-segment LED display
Tilslutning	:	Op til 10 CANopen slave-moduler, 120 kommandoer SDO/PDO

