

Robust DIN-rail fanless Embedded PC with Intel N4200 CPU, HDMI, 4 COM, LAN, 2 USB

FEATURES

Pentium® processor N4200

1 x SO-DIMM DDR3L-1866, up to 8GB

4 x DB9 Isolated RS-232/422/485

4 x USB 3.0

1 x HDMI (up to 1920 x 1200 @60Hz)

2 x RJ-45 isolated 10/100/1000 Mbps

1 x DB9 8-bit programmable DIO

Wide operating temperature range from -40°C to +70°C

12 to 24 VDC wide range power input

Dimensions 48 x 110 x 155 mm



SPECIFICATIONS

CPU	:	Intel® Celeron® N4200 4C @1.1 GHz, TDP: 6W
Storage	:	1 x mSATA (occupied 1 x PCI Express Mini Card slot), 1 x Internal 2.5" SATA drive (9.5 mm height)
Chipset	:	SoC Integrated
Video	:	1 x HDMI (up to 1920 x 1200 @60Hz)
USB	:	4 x USB 3.0
Operating Temp.	:	-40°C to +70°C
Hukommelse	:	1 x SO-DIMM DDR3L-1866, up to 8GB
Montering	:	DIN-rail, Wall Mounting
mPCIe	:	2 x Full-size Rev. 1.2 PCI Express Mini Card slot: • 1 x USB/PCIe with SIM socket • 1 x mSATA/USB/PCIe
OS SUPPORT	:	Windows® 10 IoT, Linux
Porte	:	4 x DB9 Isolated RS-232/422/485
Strømforsyning	:	1 x Terminal block, 12 to 24 VDC 12 to 24VDC, 2.82-1.34A



**DANBIT**

EPC-N4200-DIN

SPECIFICATIONS

Dimensioner : 48 x 110 x 155 mm

Certifications : CE (Class A), FCC (Class A)



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.