

SMS GSM alarm with 4 x Digital input, 4 x Analogue input, 4 x Relay outputs. Alarms for mobile phone via SMS or call, APP, 4G

FEATURES

- 4 x Digital inputs NC/NO Type
- 4 x Analog inputs. 12 bit resolution
- 0-5V, 4-20mA or 0-20mA
- 4 x Relay outputs 5A/30VDC, 5A/250VAC
- Up to 10 alarm receivers
- 1 x USB port for setup
- GSM 3G 4G mobile network
- 9-36VDC (12V / 300mA)
- Backup Battery 3.7V 1200mAh
- Operating temperature -10- + 70 ° C
- Customized SMS Alarm messages
- APP for iOS and Android
- Delivered WITHOUT SIM CARD



SPECIFICATIONS

USB	:	1 x USB
Operating Temp.	:	-10-+70 °C
Batteri	:	3.7V 1200mAH
Frekvens	:	850/900/1800/1900MHz
Indgang	:	4 Digital input, NC/NO type, one of it can be used as Pulse Counters;
Indgang	:	4 Analog Inputs. 12 bit resolution, 0-5V or 0-20mA or 4-20mA; Optional: each AIN can change to PT100 RTD inputs.
Luftfugtighed	:	Relative humidity 95% (condensation free)
Relæ	:	4 x Rated: 5A/30VDC,5A/250VAC
SIM kort	:	Standart SIM
Strømforbrug	:	Max.: 12V/300mA
Strømforsyning	:	9-36VDC
Weight	:	650g



**DANBIT**

GSM-ALARM271

SPECIFICATIONS



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.