

17" TFT-LCD Modular Panel PC with 8th Gen. Intel® Core™ U Series Processor, 9~48VDC

FEATURES

- 17" 1280 x 1024 (SXGA) TFT-LCD
- True Flat IP65 Compliant Front Panel Protection
- Resistive Touch
- Intel® Core™ i3-8145ue Dual Core Processor (4M Cache, op til 3,90 GHz) (Standard)
- Intel® Core™ i5-8365 quad Core Processor (6M cache, op til 4,10 GHz) (option)
- 2x DDR4 SO-DIMM Socket, Supports Up to 2400MHz, 64GB
- Integrated USB 3.2 Gen 2 supports up to 10Gbps
- M.2 E Key Socket for Wireless Module or Intel CRF Module
- Supports Ignition Sensing Function (IGN) (optional)
- Supports 2x PoE+ Function (optional)
- Designed with Rugged Aluminum Die-casting Front Bezel
- Supports Panel/VESA/Rack Mounting
- 9~48VDC via 3-pin Terminal Block



SPECIFICATIONS

Storage	:	2x 2.5" HDD/SSD Drive Bay (SATA 3.0), Supports RAID 0/1
USB	:	3x USB 3.2 Gen2 (Type A), 4x USB 3.0, Type-A, 2x USB 2.0 (Type A)
Operating Temp.	:	-20°C to 70°C
Andet	:	Fanless Design
DIO	:	16x Isolated DIO (8x DI/8x DO), 20-Pin Terminal Block
Forsyning	:	9~48VDC via 3-pin Terminal Block
Grafik	:	Integrated Intel® UHD Graphics 620
Hukommelse	:	2x DDR4 2400 MHz 260-Pin SO-DIMM Socket Supports up to 64 GB (un-buffered and non-ECC)
Kontrast	:	800 : 1
Lyd	:	Realtek® ALC888-GR
Lysstyrke	:	350 cd/m2
Netværk	:	2 x RJ45 (GbE1: Intel I219LM, GbE2: Intel I210IT)



SPECIFICATIONS

Porte	:	4x RS-232/422/485 with Auto Flow Control (Supports 5V/12V), DB9
Skærm	:	17" (5:4) 1280 x 1024
Touch	:	Resistive 5-wire
Udvidelser	:	2x Full-size Mini-PCIe Socket, 1x M.2 2230 E Key, 1x Front Accessible, 4x Antenna Hole SIM
Weight	:	7.9 kg
Dimensioner	:	450 x 350 x 76 mm

