

8K digital Signage Player 4xHDMI Gen. 11 CPUs FEATURES

- ISmart Intelligent energy-saving technology with Power On / Off Scheduling and Power Resume Functions
- 11th Gen Intel® Core™ U-Series Processor
- 4x HDMI 2.0 with independent audio output
- Built-in hardware Edit Emulation function
- HDMI-CEC and display monitoring functions
- 2x DDR4-3200 SO-DIMM, Dual Channel, Max. 64DK
- 1x M.2 B-Key (3042) for 4G LTE
- 1x M.2 E-Key (2230) for WiFi, Bluetooth or Capture Card Selection
- TPM 2.0, VPRO and WatchDog Timer
- Industrial-Grade Robust Fanless and Compact Design



SPECIFICATIONS

CPU	:	Socket BGA-1449, i3, i5, i7
Storage	:	1x M.2 2280 M-key supports NVMe (PCI-E x4 / SATA)
Chipset	:	Integrated
USB	:	1x USB2.0, 3x USB3.1 Gen.2
Operating Temp.	:	0°C~ 45°C (32°F~113°F)
Approval	:	CE, FCC Class B, cULus & CCC
Chok/Vibration	:	M.2: 5 grms / 5~500Hz / random operation
Ethernet	:	2xRJ45 (1 lan i219LM i5 and i7 version, i3 Intel i219V, 2 lan: I211AT)
Forsyning	:	12Vdc, max 84Watt
Grafik	:	11th Gen Intel Core U-Series Gen 12 Integrated up to 96EU
Hukommelse	:	2 x DDR4-3200 SO-DIMM, MAX. 64GB
Lyd	:	1 x Audio Connector for line out



SPECIFICATIONS

Porte	:	1x RJ45 RS232
SIM kort	:	1x UIM/SIM card slot
Udgange	:	4 x HDMI 2.0
Watchdog	:	Watchdog Timer: 256 segments, 0, 1, 2...255 (sec/min)
Weight	:	1.7Kg
Dimensioner	:	200.8mm(W) x 139.3mm(D) x 41.2mm(H) 7.90"(W) x 5.48"(D) x 1.62"(H)

