

2MP ATEX Zone 1 and 2 CLASS IIC compact IP camera
in 316L steel housing. IP68, NMEA 3X, Zoom
2.8-12mm. PoE or 12VDC

FEATURES

ATEX certified IP camera in steel housing
2 Megapixels
Motor-Zoom from 2.8 - 12mm @F1.6
NMEA-4X, IP68/IP69
H.264+/ H.264/ M-JPEG Compression
Smart Focus System with remote focus adjustment
DMR digital noise reduction
PoE Power over Ethernet, 2.88W
PoE 9W with heater on at -40°C
Day and night manual switch time control
Operating temperature -40°C - +65°C
The heater is switched on at -40°C
Micro SD Card Backup up to 64GB
2-way Audio
Support iPhone/Android/Mac
SDK for Software Integration
Free Bundle 36 Ch Recording Software
Dimensions: L145 x Ø95 mm
Weight: 3.8kg
Label length: 4 metres



SPECIFICATIONS

IP-Tæthed	:	IP68 / IP69
Kamera	:	1/28" Sony True WDR Starvis CMOS Sensor
Linse	:	2.8 - 12mm, 4.2 Zoom
Compositions	:	AIST 316L Stainless Steel
Mål og vægt	:	145 x ø95 mm, 3.8kg
Opløsning	:	1920x1080 @ 30Hz 2MP
Certifications	:	Zone 1 og 2 IIC T6 Group (Gas), Zones 21 og 22 IIIC T85 deg C

