

19" Panel PC IP65 front, Celeron, i5 or i7, 2xCOM, 2xRJ45, 9~36Vdc, 10Bit GPIO, FEATURES

19" TFT-LCD Panel PC
IP65 front
Resolution: 1280*1024
250 nits
5-wire resistive touch screen (capacitive touch on request)
Intel Celeron J4125/J6412 CPU / Core i5 /i7
RAM: 1x SO-DIMM DDR4 (celeron) max 16 GB, i5/i7 2x SO-DIMM DDR4 max 32 GB
1 x M.2 2242/2260/2280 SATA
1 x SATA (2.5" SATA)
1 x M.2 2280 NVME
MPCle: M.2 3042/3052 for 3G/4G/5G with built-in SIM slot, M.2 2230 WiFi & BT
2x RJ45 Intel i225V (on special request 2 more can be added)
USB: Celeron version: 4*USB2.0+2*USB3.0 (J4125/J6412), i5/i7 version 4*USB3.0+2*USB2.0
COM: 2x DB RS-232/422/485 port, 4*RS232 in expansion port
GPIO: 1* 10 bit GPIO Inside the expansion port
Power supply: 9-36V DC plug
Working temperature: With air flow -10 ~ 60° C
Anti-vibration with SSD: 3 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hour/axis
Anti-shock with SSD: 30 G, IEC 60068-2-27, half sine, 11 ms duration
437.27x361.27x68.8mm
OS Support: Windows 10 / Ubuntu, CentOS



SPECIFICATIONS

Memory Type	:	DDR4
Max. Memory Capacity	:	16
Power Input	:	DC 9~36V
Antal Video Udgange	:	1
Antal LAN Porte	:	2
Antal USB	:	6
Antal Serial	:	2

