

21.5" IP69K stainless PCAP chassis monitor for food and chemical industry, option 1000 nits

FEATURES

- 21.5", FULL HD 1920 x 1080 16.7m Colors
- Brightness 250nits (Possibility: 1000nits)
- IP69K
- VGA, (Possibility HDMI)
- USB for touch screen control
- PCAP Projected capacitive multitouch screen, touch with flat design
- A true flat, easy to clean front surface with edgeto-edge design
- Full IP69K waterproof enclosure
- SUS 316/ AISI 316 stainless steel for food and chemical industries
- Waterproof sealed conduit pipe for cable protection
- Support VESA / YOKE mount
- Optical bonding (Possibility)
- Operation temperature 0°C to 45°C
- 541 x 337 x 56.2 mm
- 12V DC



MON21.5-T-IP69K

SPECIFICATIONS

USB	:	1x USB typeA for touch screen control
Operating Temp.	:	0°C to 45°C
Approval	:	CE, FCC
Forsyning	:	12V DC
HDMI	:	1
IP-Tæthed	:	IP rating Full IP65/IP69K
Kontrast	:	3000:1
Luftfugtighed	:	10% to 90% RH, NonCondensing
Maks. opløsning	:	1920 x 1080
Materiale	:	Stainless Housing
Montering	:	Vesa; Yoke
Touch	:	Projected Capacitive Multi Touch Screen



MON21.5-T-IP69K

SPECIFICATIONS

Nits	:	250Nits; 1000Nits
Display	:	21.5"
Dimensioner	:	541 x 337 x 56.2 mm

