

Wireless Transmitter/Receiver for HDMI / SDI Video signal

FEATURES

- 3G-SDI and HDMI Inputs and Outputs
- Transmitter: 1x USB-C (5 VDC) Input
- Receiver: 1x USB-C (5 VDC) Input
- Live Streaming via Mobile Device & App
- Range 152.4m max (Line-of-Sight)
- HDMI/SDI
- 1080p: 60/59.94/50/30/29.97/25/24/23.98
- 1080i: 60/50
- 720p: 60/50
- Operating temp. 0 to 50°C
- Dimensions: 113 x 65 x 29.2mm



SPECIFICATIONS

Video	:	Transmitter: 1 x BNC Input Transmitter: 1 x HDMI Input Receiver: 1 x BNC Output Receiver: 1 x HDMI Output
Operating Temp.	:	0 to 50°C
Afstand	:	500' / 152.4 m (Line-of-Sight)
Formater	:	HDMI/SDI 1080p: 60/59.94/50/30/29.97/25/24/23.98 1080i: 60/50 720p: 60/50
Frekvens	:	5 GHz
Skærm	:	Transmitter: 1,3" OLED, Receiver: 1,3" OLED
Strømforsyning	:	Transmitter: 1 x USB-C (5 VDC) Input Receiver: 1 x USB-C (5 VDC) Input
Dimension	:	113 x 65 x 29.2 mm
Weight	:	200g

