

Dual-Lens 4MP People Counting Camera with POE and Digital I/O

FEATURES

- Bi-directional people counting
- Accuracy Up to 95%
- Target height filtering
- Recommended installation height is 2 to 6 meters
- Alarm trigger for crowd density counting or reverse entry detection
- Real-time, daily, weekly, monthly or annual counting reports and graphs
- 1x Input, dry contact, NO/ NC / 1x Replay Output (30V DC, 1A)
- PoE (IEEE 802.3af)
- Micro SD card slot (SD/SDHC/SDXC/UHS-I, Class 10) for local storage
- Audio jack for microphone and speaker
- IP66
- 12 languages on Web interface
- ONVIF (Profile G, S, T) conformant



SPECIFICATIONS

Operating Temp.	:	-30 °C ~ 45 °C (-22 °F ~ 113 °F)
Forsyning	:	12V DC / PoE (IEEE802.3af)
IP-Tæthed	:	IP66
LED	:	4 IR LEDs / 10 m (35 ft) max
Montering	:	2 ~6 m (6.56 ~ 19.69 ft) sealing mounting
Mål og vægt	:	563 g (1.24 lb)
Opløsning	:	2560 (H) x 1440 (V)
Sensor	:	1/3" Progressive Scan CMOS
Dimensioner	:	180 x 65 x 43.4 mm (7.08 x 2.56 x 1.71 in)
Certifications	:	CE, FCC compliant

