

Fanless PC with Intel® Core™ 14th/13th/12th Gen Processor – Optional Hailo AI Accelerator

FEATURES

- Dual DDR5 SO-DIMM memory slots (up to 96 GB)
- Optional Hailo AI accelerator via M.2 (up to 26 TOPS)
- 1x M.2 M-Key NVMe PCIe x4 (2242/2260/2280)
- 1x M.2 E-Key 2230 for Wi-Fi/Bluetooth
- 2x SATA III ports for storage expansion
- 1x HDMI and 3x DisplayPort outputs (up to 8K resolution)
- 1x 2.5GbE and 1x 1GbE RJ45 LAN ports
- 4x COM ports (2x RS-232/422/485 selectable)
- 3x USB 3.2 Gen 2 (2x Type-A, 1x Type-C), 1x USB 3.2 Gen 1, 4x USB 2.0
- 8-bit programmable GPIO header
- Line-in/Line-out audio ports (Realtek ALC897)
- Wide-range DC IN: 12-36 V via 3-pin terminal block
- Operating temperature: -20°C to 60°C
- Dimensions: 253 x 201 x 111.8 mm
- Weight: 5.25 kg
- Wall-mountable design for flexible installation



SPECIFICATIONS

CPU	:	14th/13th/12th Gen Intel® Core™ Processors in LGA1700 package (35W TDP)
Memory Type	:	DDR5
Max. Memory Capacity	:	96
Power Input	:	DC 12~36V
Video	:	- 3x DP, resolution up to 8K - 1x HDMI
USB	:	- 3x USB 3.2 Gen 2 (2x Type A+ 1x Type C) - 1x USB 3.2 Gen 1 - 4x USB 2.0
Serial	:	4x COM ports (2x RS-232/422/485)
Operating Temp.	:	-20°C ~ 60°C
Andet	:	- 2x Antenna holes for Wi-Fi module - 1x EXT Power Switch
Ethernet	:	- Intel® I210AT(1GbE) and Intel® I225LM(2.5GbE) Ethernet controller - 2x RJ45 connectors
Forsyning	:	DC 12V ~ 36V with 3-pin Terminal Block Connector
GPIO	:	1x Programmable 8-bit Digital I/O



SPECIFICATIONS

Montering	:	Wall mounting
SATA	:	2x SATAIII ports
TPM	:	TPM 2.0
Udvidelser	:	- 1x M.2 E Key 2230 with PCIe x1, CNVI for Wireless - 1x M.2 M Key 2242/2260/2280 with PCIe x4 and SATA3 for SSD
RAM	:	Up to 96GB DDR5 5600 on two SO-DIMM sockets
Dimensioner	:	253 (W) x 201(D) x 111.8 (H) mm
Antal Video Udgange	:	4
Antal LAN Porte	:	2
Antal USB	:	8
Antal Serial	:	4

