

Explosion Proof PTZ Speed Dome Camera, 4MP, 26x optical zoom, ATEX

FEATURES

ATEX Zone 1, Zone 2, Zone 21, Zone 22

Explosion-proof, anti-corrosion, waterproof
4MP 1/2.8" CMOS, up to 1080p at 25/30 fps;
H.264/H.265/MJPEG

26x optical (5-130 mm) + 16x digital; ICR
day/night; down to 0.001 lux (color) / 0.0001 lux
(B/W)

Robust PTZ: 360° pan, -18°-90° tilt, up to 250°/s
pan / 150°/s tilt, 1024 presets, tours & scans
IP66/IP68, built-in TVS 4000 V surge protection
Stainless steel 304 (optional 316/316L) for high
corrosion resistance

MicroSD/SDHC/SDXC up to 256 GB

IPv4/IPv6, HTTPS, 802.1x, RTSP, etc.; up to 20
simultaneous viewers and 32 user roles
2x DI, 1x DO, motion/audio/tamper/network
diagnostics

Working temperature: -40 to +60 °C, ≤95% RH;

Power input: DC 12V 2A

Typical uses: oil & gas, chemical plants,
marine/offshore, depots, filling stations



SPECIFICATIONS

Operating Temp.	: -40°C to 60°C
Andet	: PTZ Position Display On/Off
Beskyttelse	: IP66, IP68, Built-in surge arrester, Anti-electricity surge TVS 4000V.
Forsyning	: DC 12V 2A
Hukommelse	: Built-In Micro SD Card Slot, Support SD/SDHC/SDXC Micro Card (Max Support 256G), Support Manual/Alarm Video Recording
Luftfugtighed	: ≤ 95% (+25°C)
Montering	: Wall Hanging, Fixed Bracket, Pillar Base
Opløsning	: 50Hz: 25fps(1920×1080), 25fps(1280×720); 60Hz: 30fps(1920×1080), 30fps(1280×720)
Protokol	: IPv4/IPv6, HTTP, HTTPS, 802.1x, QoS, FTP, SMTP, UPnP, SNMP
Material	: Built-In Micro SD Card Slot, Support SD/SDHC/SDXC Micro Card (Max Support 256G), Support Manual/Alarm Video Recording
Certificate	: ATEXII 2G Ex d IIC T6 GbII 2D Ex tb IIIC IP68 T80°C Db

