

650 W ATX 3.1 Power Supply 80 PLUS Gold PS2 Format

FEATURES

Power 650 W

Form factor ATX12V V3.1

80 PLUS certification Gold, Efficiency $\geq 90\%$ at typical load

MB (Motherboard) 24-pin: 1 cable / 1 connector (550 mm)

CPU 8-pin + CPU 4+4-pin: 1 cable / 8-pin $\times 1$ + 4+4-pin $\times 1$ (755 mm)

PCIe 6+2-pin: 1 cable / 2 connectors (655 mm)

SATA connector: 1 cable / 4 connectors (965 mm)

Molex (4-pin) + additional SATA: 1 cable / Molex $\times 2$ + SATA $\times 2$ (965 mm)

+12 V rail 54.17 A


Dimensions 140 $\times$ 150 $\times$ 86 mm

Cables Not fully modular (fixed cable bundle)

Comprehensive protection functions: OVP (Over Voltage Protection), OCP (Over Current Protection), OPP (Over Power Protection), OTP (Over Temperature Protection), SCP (Short Circuit Protection), UVP (Under Voltage Protection), SIP (Surge/Inrush Protection) and NLO (No Load Operation).

Compact format: 140 $\times$ 150 $\times$ 86 mm, making it easier to integrate into smaller cabinets.

Input voltage 100-240 V AC, current 8-4 A



SPECIFICATIONS

Operating Temp.	:	max. 40°C
Beskyttelse	:	OVP, OCP, OPP, OTP, SCP, UVP, SIP, NLO
Effekt	:	650W
Indgangsspænding	:	100-240V
Form Factor	:	ATX12V V3.1
Dimensioner	:	140×150×86 mm

