

10.4" PanelPC with I3 Intel Alder Lake-N processor, Capacitive Touch, IP65 front

FEATURES

10.4" TFT-LCD SVGA display
Resolution :1024 x 768, Brightness 470 cd/m²
Intel Alder Lake-N processors I3, Intel® Core™ i3-
N305 8 Cores Up to 3.80 GHz, TDP 15W
Resistive 5-wire (on request Capacitive touch)
DDR5 SO-DIMM, max. 16 GB memory
Storage: 1x 2.5", 1x M.2
1x M.2 E for WiFi/Bluetooth
1x M.2 B for 5G/GNSS/SATA
Ethernet: 2x 2.5G
1x USB 2.0
3x USB 3.2
1x DisplayPort, 1x VGA
8xDIO, (4in/4out), 10-Pin Terminal
IP65 front panel for protection
Material aluminum
Dimension: 295 x 227.3 x 56.2 mm
Panel/VESA/Rack mount
Wide voltage 9 to 48VDC, consumption 4.99W (Typ.),
remote power ON/OFF
-20°C to 70°C (requires special components
SSD/RAM)
EMC Emission / Immunity Standard for Industrial
Environment : EN61000-6-4, EN61000-6-2



SPECIFICATIONS

Memory Type	:	DDR5
Max. Memory Capacity	:	16
Storage	:	1x 2.5" Bay & 1x M.2 Key
Power Input	:	DC 9~48V
Video	:	1x DP, 1x VGA
USB	:	3x USB 3.2 & 1x USB 2.0
Serial	:	2x RS-232/422/485
LAN	:	2x 2.5GbE LAN, RJ45
Storage Temp.	:	-30°C to 80°C
OS SUPPORT	:	Windows®11, Windows®10, Ubuntu Desktop 22.04 LTS
Skærm	:	10.4" 1024 x 768
EMC	:	CE, UKCA, FCC, ICES-003 Class A



SPECIFICATIONS

Dimensions : 295 x 227.3 x 56.2 mm

