DOORLOCK-MAG2

Electronic door lock for 12 or 24 volts, with no voltage Open

FEATURES

- Electric door lock that is open without voltage.
Holding force 1000 KG
supply: 12 / 24V DC 130 / 65mA when activated
Suitable for Scandinavian types
Operating temperature: -20 ° C to + 40 ° C
Multi voltage 12-24V AC / DC
approved for use in fire-resistant doors E120 / A120 / EI120
Fail secure (PTO): SL 620
Fail safe (PTL): SL 621
Latch bolt adjustable left / right
Built in "By status" sensor
Status monitoring: latch, anti-thrust bolt live handle
Mechanical key override

Danbit A/S Værkstedsvej 39 Køge, 4600 Denmark | +45 56662020 | salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.

DANBIT

DOORLOCK-MAG2

SPECIFICATIONS

Operating Temp.	:	-20°C till +40°C
Forsyning	:	12/24V DC 130/65mA ved aktivering
Fuld belastning	:	1000 Kg
Sensor	:	Built in ”Door Status” sensor
Sikkerhed	:	Fail secure (PTO): SL 510 Fail safe (PTL): SL 511
Certifications	:	godkendt til brug i brandsikre døre E120/A120/EI120

Danbit A/S Værkstedsvej 39 Køge, 4600 Denmark | +45 56662020 | salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.