

ESW10G8SFP

10-port managed switch 2 x 10/100/1000Mbit RJ45.  
Fiber 8 x SFP 100/1000Mbit SFP slot, DIN mounting  
12-48VDC and 24VAC

## FEATURES

- Managed switch. 8 x SFP, 2 x RJ45 ports
- 8 x fiber ports - 100/1000Base-SX / LX mini-GBIC SFP slots
- 2 x copper ports - 10/100/1000Mbit RJ45
- IP30 enclosure
- DIN rail and wall mounting
- 24:02 48V DC, redundant power
- Can accept 24VAC
- 40 to +75°C operating temperature
- Dimensions: 152 x 107 x 72 mm



**SPECIFICATIONS**

|                 |   |                                                                                                                                                                                                                 |
|-----------------|---|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating Temp. | : | -40 til +75°C                                                                                                                                                                                                   |
| Fiber           | : | 8 x 100/1000 Mbit porte til SFP                                                                                                                                                                                 |
| IP-Tæthed       | : | IP31                                                                                                                                                                                                            |
| LED             | : | Indikation af on/off, fejl, hastighed, link, og aktivitet med lysdioder                                                                                                                                         |
| Porte           | : | 2 x 10/100/1000 Mbit porte med RJ45-stik og automatisk detektering af lige/krydset kabel.                                                                                                                       |
| Relæ            | : | 1 relæudgang til alarmering ved strømforsyningsfejl                                                                                                                                                             |
| Strømforsyning  | : | Redundant indgang til strømforsyning; 2 x terminalblok til 12 - 48 VDC eller 24 VAC med polaritetsbeskyttelse.                                                                                                  |
| Tilbehør        | : | Leveres med DIN skinnebeslag, vægbeslag, manual på CD og quickguide                                                                                                                                             |
| Understøtter    | : | Understøtter QoS (Quality of Service), hvor bestemte typer netværkstrafik kan prioriteres højere end andre typer (f.eks. ved maskinstyring eller IP-telefoni). Desuden understøttes VLAN med op til 255 grupper |
| Dimensioner     | : | 152 x 72 x 107 mm (H x B x D)                                                                                                                                                                                   |

