

8 x Digital Input Wet / Dry, 8 x Digital Output Over Ethernet Modbus/TCP, 2 x RJ45 to Daisy Chain. 12 - 48VDC.

FEATURES

- Modbus / TCP I / O module with built-in Web server
- Modbus / TCP and Modbus / UDP protocols
- 2 x RJ45 Ethernet switch to Daisy-Chain topology
- Dual Watchdog
- Operating temperature range: - 25 to + 75 ° C
- I / O Pair connection - Ingang reflex in the second's exit
- 8 x Digital input: Wet (Apply Volt), Dry (Contact) -
- Digital Input: 0 - + 50VDC or Open / GND
- 8 x Digital Output, Open Collector 0 - 40VDC / 650MA
- Dimensions: 76 mm x 120 mm x 38 mm
- Supply voltage: 12 - 48vdc, 4 watt
- your bracket Wall mounting



SPECIFICATIONS

Operating Temp.	:	-25 ~ +75°C
Effekt	:	3.9 W (Max)
Ethernet	:	2 x RJ-45, 10/100 Base-TX, Switch Ports
Indgang	:	8 x Dry/Wet contact, On: +10 VDC ~ +50 VDC, Off: +4 VDC Max, Overvoltage protection: +70 VDC
Luftfugtighed	:	10 ~ 90% RH, non-condensing
Montering	:	DIN-Rail eller væg montering
Stik	:	Skrueterminaler
Strømforsyning	:	12 ~48 VDC
Udgange	:	8 x +10 VDC ~ +40 VDC, Overvoltage protection: 47 VDC
Dimensioner	:	76 mm x 120 mm x 38 mm

