

Seriel portserver til Ethernet

FEATURES

- External COM port over Ethernet and Internet.
- RS232 seriesport via DB9 Han, or
- RS422 / 485 port via screw terminal block
- Power supplied from 12 - 48VDC. Has redundant DC input.
- DIN mounting



SPECIFICATIONS

Administration	:	Indstilles via netværk over http, telenet eller via medfølgende opsætnings software
Operating Temp.	:	-10 - 60°C
Andet	:	Den Serielle port kan sende data til 10 modtagere simultant. Leveres uden strømforsyning benyt f.eks. DC24V625MA-D
Kabinet	:	IP 30 metalkabinet i format 135 x 32 x 97 mm (H x B x D)
Kompatibilitet	:	COM-driver til Windows 2000, XP, 2003, Win7 32/64 bit og Win8
Montering	:	DIN skinne og vægbeslag monteringsdele
Netværk	:	1 x 10/100 Mbit Ethernet
Porte	:	En port, der kan bruges som RS232, RS422 eller RS485. Hastigheder fra 300bit/s til 230,4 Kbit/s, Databit:5/6/7/8, Stopbit:1/1,5/2. Paritet: Lige/Ulige/Ingen
Protokol	:	TCP, UDP, Telnet, DHCP, http, DNS, SMTP
Signaler	:	RS232: TxD, RxD, DCD, RI, GND. RS422: TxD+, TxD-, RxD+, RxD-. RS485 2-leder: Data+, Data-
Stik	:	Seriell port: RS232 DB9 hanstik og RS422/485 skrueterminaler. Ethernet: 1 x RJ45 hunstik
Strømforsyning	:	Redundant spændingsforsyning: 2 x 12 ~ 48 VDC via skrueterminaler

