

1 port serial port server via Single Mode fiber, RS232 / RS422 / RS485, up to 30km. Korenix JETPORT 5601F-S

FEATURES

- External COM port via Ethernet and Internet - for fiber cable network switch
- Device server with single mode fiber and RS232/422/485 port



SPECIFICATIONS

Operating Temp.	:	-10 til 70° C
Kabinet	:	Metalkabinet. 30 x 96 x 99 mm. (H x B x D) - m/holder til DIN skinne
Netværk	:	100Base-FX via duplex SC lyslederkabel. Til singlemode fiber - maks. 30 km
Porte	:	1 x RS232/422/485 port med hastigheder fra 110 bps til 460 Kbps på DB9-stik. Databit: 5/6/7/8, Stopbit: 1/2 Paritet: Lige/Ulige/Ingen. Flowkontrol: RTS/CTS, DTR/DSR, Xon/Xoff
Protokol	:	TCP, UDP, HTTP, HTTPS, Telnet, DHCP, ICMP
Signaler	:	RS232: TxD, RxD, RTS, CTS, DTR, DSR, RI, GND. RS422 og 4-tråds RX485: Rx+, Rx-, Tx+, Tx-, GND. RS485: Data+, Data-, Rx+, GND
Skærm	:	Lysdioder viser Tx/Rx, netværks- og Power-tilstande
Software	:	Windows 2000,XP, 2003 ,Vista, Windows 7 32 bit
Strømforsyning	:	12 - 48 VDC på skrueterminaler eller 9 - 30 VDC på DC jack (230 V adapter medfølger)

