

6 x Digital input, 6 x Relay output via Ethernet for industrial control applications. 2 x RJ45 daisy chain PoE

## FEATURES

- 6 x Digital Inputs - Wet (active at DC in)
- 6 x Power relay outputs - 24VDC / 250VAC / 5A
- Protocol: Modbus TCP / UDP
- 2 x RJ45 Ethernet interface
- With built-in network switch - with the daisy chain I / O Pair-function - the input is mirrored to the second output
- Digital inputs with counter - max 500Hz
- the minimum pulse width: 1 ms
- Screw terminal
- Supply voltage: PoE or 10 - 30VDC / 3watt
- PoE is NOT continued to LAN port 2 (data only)



## SPECIFICATIONS

|           |   |                                                                                                     |
|-----------|---|-----------------------------------------------------------------------------------------------------|
| Forsyning | : | 10 - 30 VDC, 2,5 W via klemrække eller PoE                                                          |
| Indgang   | : | 6 stk. digitale Logisk 0: 0 - 4 VDC, Logisk 1: 10 - 50 VDC                                          |
| Netværk   | : | 10/100 Mbit m/RJ45-stik                                                                             |
| Protokol  | : | Modbus/TCP, TCP/IP og UDP                                                                           |
| Tæller    | : | Indgange kan virke som 32 bit tæller, maks. frekvens 500 Hz                                         |
| Udgange   | : | 6 stk. relæudgange: AC: 250 V og 5 A eller DC: 30 V og 5 A. Skiftetider<br>Lukke/åben er 7ms / 3 ms |

