

I775-Q35

Older CPU card Socket LGA775 CPU PICMG 1.3 Q35
Chipset, WINDOWS 2000, XP, VISTA, Windows 7
support IB935

FEATURES

Q35 chipset Core 2 Quad/ CORE 2 DUO / Celeron
400 sequence processor (conroe-L)
LGA 775 FSB 800 / 1066 / 1333 MHz
2 x Gigabit Lan, (Intel 82566DM, Intel 82574L)
VGA (GMA 3100), CRT support
SATA II
Parallel port LPT
2 x COM
4X USB 2.0
OS SUPPORT: Windows 2000, Windows XP, Windows
VISTA, Windows 7.



SPECIFICATIONS

CPU	:	Intel Core 2 Quad/Duo, Celeron 400 serien. LGA775 sokkel
Chipset	:	Intel Q35 / ICH9
Digital I/O	:	4 indgange og 4 udgange (TTL)
USB	:	4 x USB 2.0 (Hi-Speed)
Operating Temp.	:	0 - 60o C ved 10 - 90 % ikke-kondenserende luftfugtighed
BIOS	:	4 Mbit Award flash BIOS med ACPI understøttelse
Drev	:	1 x ATA/66/100/133, 4 x SATA300
FSB	:	800/1066/1333 MHz
Grafik	:	Integreret Intel GMA3100 (1 x DB15HDF VGA-stik)
Hukommelse	:	2 x 240-pin (dual channel) DDR2 maks. 4 GB, PC2-5400/6400
Interface	:	1 x FDD diskettecontroller til to 3½" eller 5¼" drev (maks. 2,88 MB)
Lyd	:	ICH9 AC97 Codec



SPECIFICATIONS

Overvågning	:	System/CPU - temperatur og - spænding
Porte	:	1 x SPP/EPP/ECP, bi-direktionel, med 1 x DB25F-stik
Porte	:	1 x RS232 (DB9M), 1 x RS232/422/485 (DB9M)
RAID niveau	:	PICMG 1.3 (PCI Express)
Strømforsyning	:	Via PICMG bussen og ATX 12V stik (Se kapitel 19 for strømforsyninger)
Tastatur/mus	:	2 x mini-DIN6 PS/2 via Y-splitterkabel (medfølger)
Watchdog	:	Op til 255 sekunders timeout

