

15" panel PC 6 th Gen. i3 / i5 (option) processor with
Touch IP66 front

FEATURES

- Build To Order
- 15" TFT-LCD
- CPU i3 (i5 option)
- Max. res. 1024x768
- Touch projected Capacitive Touch
- 4GB DDR4 RAM (Max. 16GB)
- 2 x USB
- 2 x RJ45 Lan
- 1 x RS232/422/485, 1 x RS232
- IP65 front
- OS support: Win. Embedded Compact 7,
Win 7 / 7 Pro, Win 7 Ultimate, Win Emb. 8.1
Industry Pro
- Windows 10 IoT



SPECIFICATIONS

CPU	:	Onboard Intel 4th Gen. Core i3 CPU (option i5)
Storage	:	1 x 2.5" SATA Bay, 1 x SD card slot max. 32GB
USB	:	2 x USB 3.0 type A
Operating Temp.	:	temperature(°C) 0~50°C, -20~60°C (option)
Andet	:	Optioner: 2 x CAN 2 x USB 2.0 type A + 1 x Mini-PCle slot + 1xRS-232 DB-9 via TB-528C1U2P1, 2 x USB 2.0 type A , UPS battery 21W/10.8V/1.95Ah
Ethernet	:	2 x GbE LAN RJ-45
Forsyning	:	DC 9~36V 1 x 3-pin DC Power input terminal / 1 x 2-Pin Power Switch
Hukommelse	:	Onboard 4GB DDR4L / max 8GB
LCD	:	15" TFT-LCD Max. resolution 1024 x 768 Max. color 16.7M Luminance(cd/m²) 420 Viewangle(H°/V°) 160/160 Backlight lifetime(hrs) 50,000
Luftfugtighed	:	10 to 90%@ 40°C, non-condensing
Lyd	:	1 x Audio Line Out
Montering	:	Panel Mounting / VESA 100 x 100



SPECIFICATIONS

Porte	:	1 x DB9 RS232/422/485, 1 x RS232 DB9
Touch	:	Projected Capacitive Touch, USB
Dimensioner	:	410mm x 310mm x 54.7mm

