

1 port serial server RS232 / RS422 / RS485. Serial Device Server RJ45, DB9 han, 9 - 30VDC

FEATURES

- Ekstern COM-port over Ethernet og Internet RS232/422/485
- Baud rate: 1200 - 230,4kbps (2-wire)
- Maks. baudrate ved 4-wire RS485 op til 921,6kbps
- Atop SE5201-DB Serial Device Server
- 10/100Mbit Ethernet.
- Serielport via DB9 han stik
- Understøtter TCP-server/Client, UDP, Virtual COM og Tunneling-tilstande
- Strømforsynes fra 9 - 30VDC eller 5VDC (power-jack)
- Strømforsyning medfølger ikke
- DIN-kit (option)
- Dimensioner: 65 x 78 x 28mm (uden vægbeslag)
- Dimensioner: 88.5 x 84 x 27.8mm (med vægbeslag og DB9 port)



SPECIFICATIONS

Driftstemperatur	:	-40°C ~ 70°C
Montering	:	Wall-Mount or DIN-Rail (optional kit)
Netværk	:	10/100 Mbit Ethernet
OS SUPPORT	:	Windows / Linux
Porte	:	RS232 / 422 / 485
Protokol	:	TCP, IPv4, UDP, DHCP Client, HTTP, HTTPS, Telnet, ARP, SNMPv1,v2c,v3
Skærm	:	3 lysdioder viser Tx/Rx, netværks- og systemstatus
Stik	:	3-Pin 5.08mm Lockable Terminal Block, DC Jack (for redundancy), RJ45 10/100 Ethernet, DB9 serial
Strømforbrug	:	Less than 1.5W
Vægt	:	185g
Dimensioner	:	65 x 78 x 28mm (without wall-mount part), 88.5 x 84 x 27.8mm (with wall-mount part and DB9 connector)

