

16-CH Latching Relay Outputs & 16-CH Isolated DI Card, PCIE

FEATURES

NY MODEL MED PCIe

Understøtter en PCI Express x1, Plug and Play (PCIe-7256)

16-CH låsende SPDT relæudgange

Energibesparelse ved relæaktivering

Output status uændret, når strømmen er slukket

On- LED-indikatorer for relæstatus

16-CH isolerede DI

Afbrydelse af status (COS) afbrydelse / Board ID

Windows 7/10 64/32 bit support

Linux i686



SPECIFICATIONS

Driftstemperatur	:	0C ~ 60C
Hastighed	:	Relay ON/OFF operate / Release time 3 ms
Indgang	:	16 isolated 0-24V high(10-24V) Low (0-2V)
Indgangsimpedans	:	4.7k Ohm @ 0.5 W
Isolation	:	Voltage 1500Vrms
Isolationsspænding	:	2500 Vrms chanel to system
OS SUPPORT	:	Windows 7/10 64/32 bit support Linux i686
Stik	:	DB68MM female
Strømforbrug	:	Typisk +3.3V (36.3mA, MAx. 980mA), +12V (141mA, Max 464mA)
Udgange	:	16 skifterelæer ("klæbe-relæer") Belastning: 250 VAC 5 A eller 30 VDC 1 A Skiftetid: typisk 3 ms
Dimensioner	:	165 mm x 107 mm (6.82" x 4.17")

