

19" LCD monitor med 300-nits, med multi-touch, støv og spuletæt IP66, IP20 bagside, dual AC/DC inputs, FEATURES

19" LCD metal monitor, IP66 foran, IP20 bagside
1280 x 1024

300 nits 2000:1, 5:4

LED backlight

Responstid: 20ms

visnings vinkel: 178°/178°

1 x RS-232 (DB9 male)

1 x DVI-D (29-Pin DVI-D female)

1 x VGA (15-Pin D-sub femlæ)

1 x RS232/422/485 (software selectable terminal block)

Capacitive touch (PCAP), 4 Points

Forsyning: 100 to 240 VAC, 24 VDC (18 to 30 V)

-15 to 55°C (5 to 131°F)

429 x 387 x 75 mm

Vægt: 7,800 g

RoHS, CRoHS, WEEE

Optional: RS-232: TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND

Optional: RS-422: Tx+, Tx-, Rx+, Rx-, GND

Optional: RS-485-2w: Data+, Data-, GND

Optional: RS-485-4w: Tx+, Tx-, Rx+, Rx-, GND



SPECIFICATIONS

Antal farver	:	16.7M (8-bit/color)
Forsyning	:	100 to 240 VAC, 24 VDC (18 to 30 V)
I/O	:	1 x DVI-D, 1 x VGA
Kontrast	:	2000:1, 300 cd/m2, 5:4
Porte	:	1 x RS-232, RS-232/422/485 ports x 1, software-selectable (terminal block)
Touch	:	Multi-touch, 4 points
Vægt	:	7,800 g
Dimensioner	:	429 x 387 x 75 mm
Certifications	:	IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV IEC 61000-4-6 CS: 1k V

