

10.1" LCD monitor, VGA og HDMI, Full IP66/IP69K,  
vandalsikker, PCAP multi touch

## FEATURES

- 10.1" LCD skærm
- 1 x VGA
- 1 x HDMI
- 1 x USB (touch)
- PCAP multitouch (USB)
- Opløsning: 1280 x 800 @ 60Hz, 75Hz
- Lysstyrke: 350 nits (cd/m2)
- OSD funktion
- Kontrast: 800:1
- Full IP66/69K samt vandalsikker
- Driftstemp. 0 - +50 C°
- Forsyning 9-36VDC, 15W
- Til VESA75 eller panelmontering
- 220 x 300 mm (H x B)



## SPECIFICATIONS

|                  |   |                                                                                                                                       |
|------------------|---|---------------------------------------------------------------------------------------------------------------------------------------|
| Driftstemperatur | : | 0 - +50C°                                                                                                                             |
| Antal farver     | : | 16.7M Colors                                                                                                                          |
| Forsyning        | : | 1 x AC/DC Power adapter, 9~36V DC or 100~240V AC Power Input (optional)                                                               |
| Interface        | : | x VGA (M12 connector) 1 x HDMI (IP66 HDMI connector) U1 x USB for touch (M12 connector) Power Input :1 x 12V DC input (M12 connector) |
| IP-Tæthed        | : | Full-IP66/IP69K                                                                                                                       |
| Kontrast         | : | 800 : 1 (typ.)                                                                                                                        |
| Lysstyrke        | : | 350 nits (cd/m2)                                                                                                                      |
| Materiale        | : | Stainless Steel                                                                                                                       |
| Montering        | : | 75x 75 VESA Mount. Panel mount for optional                                                                                           |
| Opløsning        | : | 1280 x 800 @ 60Hz, 75Hz                                                                                                               |
| OSD              | : | 5-key OSD buttons • OSD Function : Contrast, Color, Position, Auto-adjustment, Factory Settings                                       |
| Pixels           | : | Pixel Pitch (mm) : 0.2125(H) x 0.21525(V)                                                                                             |



## SPECIFICATIONS

|              |   |                                  |
|--------------|---|----------------------------------|
| Strømforbrug | : | 15W typical, normal operation    |
| Tilbehør     | : | Power Cord : 1 x 1.5m power cord |
| Touch        | : | P-cap multi-touch (USB)          |
| Type         | : | 10.1" LCD                        |
| Dimensioner  | : | 220 x 300 mm (H x B)             |

