

19" Panel PC IP65 front, Celeron, I5 eller I7, 2xCOM, 2xRJ45, 9~36Vdc, 10Bit GPIO, FEATURES

19" TFT-LCD Panel PC

IP65 Front

Opløsning: 1280*1024

250 nits

5-leder resistiv berøringsskærm (capacitive touch efter anmodning)

Intel Celeron J4125/J6412 CPU / Core i5 / i7

RAM: 1x SO-DIMM DDR4 (celeron) maks. 16 GB,

i5/i7 2x SO-DIMM DDR4 maks. 32 GB

1 x M.2 2242/2260/2280 SATA

1 x SATA (2,5" SATA)

1 x M.2 2280 NVME

M.2 PCIe: M.2 3042/3052 til 3G/4G/5G med indbygget SIM-slot, M.2 2230 WiFi & BT

2x RJ45 Intel i225V (på særlig anmodning kan 2 mere tilføjes)

USB: Celeron version: 4*USB2.0+2*USB3.0

(J4125/J6412), i5/i7 version 4*USB3.0+2*USB2.0

COM: 2x DB RS-232/422/485 port, 4*RS232 i udvidelsesport

GPIO: 1* 10 bit GPIO Indenfor udvidelsesporten

Strømforsyning: 9-36V DC stik

Arbejdstemperatur: Med luftstrøm -10 ~ 60° C

Antivibration med SSD: 3 Grms, IEC 60068-2-64, tilfældig, 5 ~ 500 Hz, 1 time/akse

Anti-chok med SSD: 30 G, IEC 60068-2-27, halv sinus, 11 ms varighed

437,27x361,27x68,8 mm

OS Support: Windows 10 / Ubuntu, CentOS



SPECIFICATIONS

Memory Type	:	DDR4
Max. Memory Capacity	:	16
Power Input	:	DC 9~36V
Antal Video Udgange	:	1
Antal LAN Porte	:	2
Antal USB	:	6
Antal Serial	:	2

