

Intel® 12th / 13th Gen Core™ Fanless Edge AI-computer, der understøtter Nvidia® RTX-A2000 m/2x10G POE'er

FEATURES

Ventilatorløst design (indlejret varmerørskøleløsning)
12/13 generation Core™ i9/i7/i5/i3-processor (Alder Lake-S/Raptor Lake-S)
Op til 60W GPU MXM-moduludvidelse
802.3af (15.4W)/802.3at(25.5W) Gigabit PoE-porte
DP x2 + HDMI x 1 og DVI x 1 (understøtter 4 uafhængige skærme)
On/off forsinkelseskontrol / konfigurerbar tændstrømskontrol
Understøtter TPM 2.0 og Time-Sensitive Networking (TSN)
To mPCIe til valgfri WiFi/3G/4G/GPS eller I/O-udvidelse understøttet
Front-tilgængelig I/O
1 x M.2 B til opbevaring eller 5G/LTE +1 x M.2 E-nøgle til WiFi/BT
1 x M.2 M til NVMe SSD
285x230x 90 mm (9,84" x11,50" x 3,54"), blæserløs
285x230x110 mm (9,84" x11,50" x 4,33"), m/ VENTILATOR
DC 9~36V indgang
CE, FCC klasse A, E-mærke
ekstraudstyr



SPECIFICATIONS

CPU	:	i9/i7/i5/i3
Memory Type	:	DDR5
Max. Memory Capacity	:	64
Storage	:	2x2.5; 2x m.2;
Chipset	:	R680E
Digital I/O	:	1 x DB15 conn.for 8 x digital input (Dry/ Wet contact) with 2KV isolation. 1 x DB15 conn.for 8 x digital output with 2KV isolation.
Power Input	:	DC 9~36V
USB	:	8 x USB 3.2/ 2.0 ports
Driftstemperatur	:	-20 ~ 50°C (-4 ~122°F), ambient w/ air flow -20 ~ 60°C (-4 ~140°F), ambient w/ air flow (w / External SMART FAN kit)
Approval	:	CE, FCC Class A, E mark
Chok/Vibration	:	IEC 60068-2-64, IEC60068-2-27
DVI	:	1



SPECIFICATIONS

Forsyning	:	DC 9~36V
Grafik	:	Integrated Intel® HD Graphics 770
HDMI	:	1
Luftfugtighed	:	10 ~ 95% @ 60°C
M.2	:	2
Materiale	:	Amininum
Montering	:	Wall-mount
mPCIe	:	2
OS SUPPORT	:	Windows 10 IOT Enterprise 64-bit; Linux (Ubuntu 20.04)
PoE	:	8
SATA	:	2



SPECIFICATIONS

TPM	:	Onboard TPM 2.0
Dimension	:	(W x D x H) 285x230x 90mm (9.84" x11.50" x 3.54"),Fanless 285x230x110mm (9.84" x11.50" x 4.33"),w/ FAN
Vægt	:	5.83Kg
Antal Video Udgange	:	4
Antal LAN Porte	:	4
Antal USB	:	8
Antal Serial	:	4

