

## Wi-Fi 6 Dual Band Wireless Access Point 3000 Mbps med PoE og 2 LAN-porte

### FEATURES

Dual Band 802.11ax 3000 Mbps Loftmonteret  
trådløst adgangspunkt  
Maks. trådløs hastighed på 2400 Mbps (5 GHz) og  
600 Mbps (2,4 GHz)  
Understøtter op til 256 samtidige klientbrugere  
2 x 10/100/1000BASE-T RJ45 port  
4 x intern 4dBi-antenne (2,4G x2, 5G x2)  
Tilstande: AP, Gateway, Repeater  
WPA3 / WPA2 / WPA-understøttelse  
Loftsmontage  
Mål: 185,82 x 185,82 x 36,6 mm  
Understøtter 48V DC PoE og 12V DC input  
Driftstemperaturområde: -20 til 55°C  
Vægt: 380 g



## SPECIFICATIONS

|                |   |                                                                                                                                                                                                                               |
|----------------|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LAN            | : | 2 x 10/100/1000BASE-T RJ45 port                                                                                                                                                                                               |
| Antal          | : | 256 clients (200 is suggested, depending on usage)                                                                                                                                                                            |
| Antenne        | : | 4 x Internal 4dBi antenna (2.4G x2, 5G x2)                                                                                                                                                                                    |
| Båndbredde     | : | 20MHz, 40MHz, 80MHz, 160MHz                                                                                                                                                                                                   |
| Forsyning      | : | 48V DC IN, 0.5A, IEEE 802.3at PoE+ (WAN/PoE were changed port) 12V DC IN, 1.5A from DC Jack (5.5 x 2.1mm)                                                                                                                     |
| Modes          | : | Access Point Gateway Repeater WISP Mesh                                                                                                                                                                                       |
| Montering      | : | Ceiling Mount                                                                                                                                                                                                                 |
| Sikkerhed      | : | WPA3 Personal, WPA2/WPA3 Personal, WPA2 Personal (AES), WPA2 Personal (TKIP), WPA2 Personal (TKIP+AES), WPA/WPA2 Personal (AES), WPA/WPA2 Personal (TKIP), WPA/WPA2 Personal (TKIP+AES), WPA2 Enterprise, WPA/WPA2 Enterprise |
| Dimensioner    | : | 185.82 x 185.82 x 36.6 mm                                                                                                                                                                                                     |
| Certifications | : | CE, RoHS                                                                                                                                                                                                                      |

