

4 ports splitter SDI, SD-SDI, HD-SDI, 3G-SDI. 1 x BNC inputs and 4 x BNC output. Same output image. 5VDC FEATURES

4 Port SDI multimedia splitter
same image on the four monitors up to 100 meters
Compatible with SD-SDI, HD-SDI and 3D SDI to 5 x BNC female
1 x BNC - SDI input to 4 x BNC - SDI output
SD 525i and 625i
HD 720p 24/25/30/50/60Hz, HD 1080i 50/60Hz
HD 1080p 24/25/30/50/60Hz
Supply voltage: 5VDC PSU included
Dimensions: 130 x 77 x 24 mm



SPECIFICATIONS

Operating Temp.	: 0~+60 °
Afstand	: p til 100 m kabellængde v. 3G-SDI (2,97 Gb/s) på ind- og udgangene
Andet	: Power consumption: 250mA (DC 5V)
Kompatibilitet	: SD-SDI, HD-SDI og 3G-SDI
Opløsning	: Op til 1920 x 1080i/p ved 60 Hz
Output	: SDI signal output amplitude: 800mVp-p
Strømforsyning	: Forsynes af medfølgende 5 VDC 1 A netadapter
Udgange	: 4 x BNC hun, indgange: 1 x BNC hun
Dimensioner	: 130 x 77 x 24mm (L x W x H)

