

8 x RS232 serielle porte til PCI, XP / Vista / 7 / 8.x /
10 (X86/X64) / 11,

FEATURES

Expands 8 independent RS-232 serial port with communication speeds up to 115.2Kbps.
High reliability SUN1999 16C950 compatible UART controller on-board.
Compliance with PCI 33MHz Ver. 3.0/2.3/2.2/2.1 specification.
Supports both 64-bit & 32-bit PCI bus slot and 3.3V & 5V power.
On-chip hardware auto flow control to guarantee no data loss.
Built-in ± 2 KV ESD protection for all serial signals.
Plug-n-Play, I/O address and IRQ assigned by BIOS.
Certified by CE, FCC, RoHS, and Microsoft WHQL approval.
Support Microsoft Windows, Linux, and DOS.
Windows ClientXP / Vista / 7 / 8.x / 10 (X86/X64) / 11
Windows Server2003 / 2008 / 2012 / 2016 / 2019 / 2022 (X64)
Windows EmbeddedXP Embedded / POSReady 2009 / POSReady / Embedded System 2009
LinuxLinux 2.x / 3.x / 4.x / 5.x / 6.x
DOSDOS***UNIX**FreeBSD / QNX / SCO OpenServer / SCO UnixWare / Solaris***IBM OS/2**WARP 3/WARP 4



SPECIFICATIONS

Andet	:	Maks. 1 kort i hver pc
Baudrate	:	Maks. 921,6 Kbit/s
Drivere	:	Windows 2000, XP, Win7, Win8, 2003, Vista og Linux
FIFO	:	32 bytes
PCI	:	3,3 og 5 V. Kompatibel med PCI-X
Porte	:	8 x RS232
Stik	:	8 x DB9 han (via blækspruttekabel der medfølger)
UART	:	16C650

