

Atomur, GPS styret tidsserver NTP-Server til netværk. Dual-LAN med TCXO

FEATURES

- Atomur- GPS styret tidsserver til netværk
- 32 kanals modtager som reducerer risikoen for signal tab
- TCXO (Temperatur Compensated X-tal Oscillator) for at holde tiden ved manglende GPS-signal
- 10/100BaseT redundant Ethernet
- Lavt strømforbrug kun 7W
- 230VAC 50-60Hz 0.1A
- Driftstemperatur 0 - 50 °
- Leveres med multi-antenne, vægmontering og 30 m RG58 antennekabel



SPECIFICATIONS

Driftstemperatur	:	0-50°C
Andet	:	Timing: GNSS Accuracy: 15 nsec (15x10 ⁻⁹ sec, GPS Lock) NTP Accuracy (GPS Lock): usec (3x10 ⁻⁶ sec) TCXO Holdover 24 Hours (after 24 hrs continuous GPS lock): ±4.3 msec (25°C) ±164 msec (0°C-40°C)
Antenne	:	T-3740 GNSS Multi-Constellation Antenna
Forsyning	:	230VAC 50-60Hz 0.1A
GPS	:	GPS/GNSS Timing Receiver 32 Channel Multi-GNSS receiver. GPS, GLONASS, Beidou, Galileo*1. Time-Receiver
Interface	:	Dual 10/100 Mbit Base-T, RJ45, Auto-Sensing Network Interfaces. TNC RF Connector For Active GPS/GNSS Antenna. USB port for firmware updates. RS232 Console Port for Configuration and Status. Second RS232 (shared) Port for serial time code output.
Kabel	:	30m RG58 Cable.
Kabinet	:	1U High 19" Rack-mount, Aluminium
LED	:	40 character x 2 line LCD display. Red/Green Alarm LED.
Protokol	:	Internet Protocol (IP) IPv4, IPv6. Timing Protocols: NTP v2 (RFC 1119), NTP v3 (RFC 1305), NTP v4 (RFC 5905). SNTP v3 (RFC 1769), SNTP v4 (RFC 2030). NTP Peering, NTP Broadcast. NTP MD5 Authentication.
Software	:	Flash-Based Linux Operating System with PPS Extensions.
Vægt	:	1.2Kg



**DANBIT**

ATOMUR-SAT-TRD+

SPECIFICATIONS



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.