

17" Panel PC, Steel front, Gen. 12/13/14, i3/i5/i7/i9.  
1xPCIe (x16) expansion, 4xCOM, Resistive Touch,  
USB, 8 DIO

## FEATURES

17" TFT LCD (LED) resolution 5:4 1280x1024 FLAT PANEL  
SUS304 Stainless Steel  
Intel® 14th/13th/12th Gen.  
Core™ i9/i7/i5/i3 Pentium® Celeron® up to 35W  
Resistive touch. (on request: Capacitive /projected)  
6 x USB  
1 x DP  
1 x HDMI  
4 COM ports  
DDR5 up to 64GB  
2 x 2.5" SATA III SSD  
1 x PCIe (X16) Slot ½ length, 1 x M.2 2230-E, 1 x M.2 3042-B, 1 x M.2 3042-B, 1 x MXM Type A  
2 x GBE LAN, Support Wake-on-LAN, PXE  
TBD  
OS Support Windows 10 IoT LTSC 2021, Windows 11 IoT Enterprise GAC Ubuntu 22.04 (kernel: 5.15)  
Front panel IP65 Protection  
-20°C~70°C, (with wide temperature SSD)  
Removable HDD / SSD Drive Bay  
VESA 75 , Panel mounting  
DC In 12/24V  
CE / FCC



## SPECIFICATIONS

|                 |   |                                                                                                                                |
|-----------------|---|--------------------------------------------------------------------------------------------------------------------------------|
| CPU             | : | Core i7-7700T, i5-7500T, i3-7101TE, Cel. G3930TE                                                                               |
| Storage         | : | 2x2.5" SATA III HDD/SSD (support RAID 0/1 in q170 SKU ONLY)                                                                    |
| Chipset         | : | Intel Q170/H110                                                                                                                |
| USB             | : | 4xUSB 3.0, 4x USB2.0                                                                                                           |
| Operating Temp. | : | Operating Temp. HDD: 0°C~45°C (32°F~113°F) (Ambient with airflow) SSD: 0°C~50°C (32°F~122°F)                                   |
| LPT             | : | 1 x Parallel port (SSP/EPP/ECP)                                                                                                |
| Antenne         | : | 2 x antenne holes (no antennae incl.)                                                                                          |
| Approval        | : | CE/FCC                                                                                                                         |
| Ethernet        | : | 2 x RJ45 ports LAN 1: Intel® PHY I219LM (10/100/1000 Mbps) LAN 2: Intel® LAN 210AT (10/100/1000 Mbps) Support Wake-On-LAN, PXE |
| Hukommelse      | : | 3xDDR4 2133MHz So-DIMM (max 32GB)                                                                                              |
| IP-Tæthed       | : | IP65 FRONT ONLY                                                                                                                |
| LCD             | : | 17" TFT LCD (LED) 5:4 SXGA                                                                                                     |



## SPECIFICATIONS

|              |   |                                                                                                                       |
|--------------|---|-----------------------------------------------------------------------------------------------------------------------|
| Compositions | : | FRONT Stainless steel                                                                                                 |
| Montering    | : | Panel Mount, Wall mount, VESA 75/100                                                                                  |
| mPCIe        | : | 1x Half size                                                                                                          |
| Opløsning    | : | SXGA 1280x1024                                                                                                        |
| OS SUPPORT   | : | Windows 10 IoT enterprise (64 bit)                                                                                    |
| Porte        | : | 4 COM ports COM 1 for RS-232/422/485 COM 2/COM 3/COM 4 for RS-232<br>COM 1/COM 2/COM 4 support +5V/+12V/RI selectable |
| Touch        | : | Resistive touch. (option: Capacitive /projected)                                                                      |
| Udgange      | : | 2 x DVI-D                                                                                                             |
| Udvidelser   | : | 1 x PCIe (x16)                                                                                                        |
| Watchdog     | : | 1~255 sec. timer selectable                                                                                           |
| Weight       | : | 9.1 KG                                                                                                                |





**DANBIT**

IPP17I+PCIE+STEEL

## SPECIFICATIONS



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.