

8 x Digital input Wet / Dry, 8 x Digital output over Ethernet Modbus/TCP, 2 x RJ45 til Daisy chain. 12 - 48VDC

FEATURES

- Modbus/TCP I/O modul med indbygget WebServer
- Modbus/TCP og Modbus/UDP protokoller
- 2 x RJ45 Ethernet-switch til Daisy-Chain-topologi
- Dual Watchdog
- Driftstemperaturområde: -25 til +75°C
- I/O pair-forbindelse - ingang spejler sig i andens udgang
- 8 x Digital input: Wet (tilfør volt), Dry (kun kontakt)
- Digital input: 0 - +50VDC eller Open/Gnd
- 8 x Digitale outout, Open Collector 0 - 40VDC / 650mA
- Dimensioner: 76 mm x 120 mm x 38 mm
- Forsyningsspænding: 12 - 48VDC, 4 Watt
- DIN-beslag væg montering



SPECIFICATIONS

Driftstemperatur	:	-25 ~ +75°C
Effekt	:	3.9 W (Max)
Ethernet	:	2 x RJ-45, 10/100 Base-TX, Switch Ports
Indgang	:	8 x Dry/Wet contact, On: +10 VDC ~ +50 VDC, Off: +4 VDC Max, Overvoltage protection: +70 VDC
Luftfugtighed	:	10 ~ 90% RH, non-condensing
Montering	:	DIN-Rail eller væg montering
Stik	:	Skrueterminaler
Strømforsyning	:	12 ~48 VDC
Udgange	:	8 x +10 VDC ~ +40 VDC, Overvoltage protection: 47 VDC
Dimensioner	:	76 mm x 120 mm x 38 mm

